




175

Reciprocating Sammying Machine – 3000MM

## MODEL NO.175 RECIPROCATING SAMMYING MACHINE.

The most important features of 3H No.175 Reciprocating Sammying machines as followed:

- Smooth passage with the least possible wrinkles.
- The speed of passage is adjustable 3~18 m/min.
- A large diameter high pressure special rubber roller avoids pleating during the feeding in towards the pressure section and keeps the felt band long life.
- The construction allows replacing the felt conveyor within a minimum of time. Neither the rollers nor heavy machine parts have to be removed. The machine is easy to be serviced and has only a few lubrication points hydraulic needs no service at all. All the rollers are running in double rollers bearings, which are packed according to the requirements.
- The running-in area is equipped with a safety device, which stops the machine immediately when being pushed.
- On the feeding-in side locked safety switches are installed to effect a stop of the machines when set going.
- With excellent processing quality, perfect stretching of the leather, simple maintenance, long lasting felts which are easy to change.
- With extremely strong and compact steel structure.
- Stretching roll with perfect stretching of leather and reduce wrinkles on hides and timed automatic return to resting position.
- Stretching roller with stainless steel blades having special design profile.
- All transmission rollers by rubber covering is guaranteed long life.
- Hydraulic control box with special pressure pump, guaranteeing a constant and even working pressure.
- The total pressure is infinitely adjustable: 0-18 Tons.



- |                           |                     |
|---------------------------|---------------------|
| 1. Setting Blade Cylinder | 4. Felt Steeve      |
| 2. Support Rubber Roller  | 5. Spreiding Roller |
| 3. Feed Pressure Roller   | 6. Leather          |

### 3H MACHINE CO., LTD.

WEB: [WWW.3HMACHINE.COM](http://WWW.3HMACHINE.COM)

E-MAIL: [h3h3h3h@ms24.hinet.net](mailto:h3h3h3h@ms24.hinet.net)

No.190, Yujhong Rd., East District,  
Tainan City 701, Taiwan

TEL: +886-6-3312207 FAX: +886-6-3312285

MOBIL PHONE: +886-955-267823

Technical Data	
Working width	3000mm
Attendance	2 operator
Feed speed (Speed Variation)	0~24 m/min
Sammying Pressure (Pressure variable)	18 Tons
<b>Total Power required</b>	33.75 Kw (45HP)
Net Weight.	8200 KGS